PATENT ABSTRACT DATABASES

[your invention]

G21130

9/5/1 (Item 1 from file: 350)

DIALOG(R)File 350: Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0014515736 Drawing available

WPI Acc no: 2004-697671/200468

Related WPI Acc No: 2000-672590; 2003-331360; 2003-429690; 2003-492021; 2003-556633; 2003-598999; 2003-618801; 2003-636908; 2003-709140; 2003-744465; 2003-778053; 2003-801037; 2003-

801549; 2003-801728; 2003-854288; 2003-875004; 2004-031547; 2004-281382; 2004-281385; 2004-303692; 2004-303895; 2004-303896; 2004-303896; 2005-194195; 2005-423462; 2005-629019; 2006-

401350; 2006-536416; 2006-576334; 2006-600989; 2007-148599; 2007-157336; 2007-523208; 2007-673842; 2007-843365; 2008-A96344; 2008-F30393; 2008-F81867; 2008-M99741; 2009-F10793; 2009-

Digital video and audio content providing method, involves producing Internet protocol datagram with header and segmented body having packets with identifiers, and transmitting datagram from head-end to divital device.

Patent Assignee: CANDELORE B L (CAND-I); SONY ELECTRONICS INC (SONY)

Inventor: CANDELORE B; CANDELORE B L

		Patent Fan	nily (5 patents, 107 cou	untries)		
Patent Number	Kind	Date	Application Number	Kind	Date	Update	Type
US 20040181666	A1	20040916	US 2001296673	P	20010606	200468	В
			US 2001304131	P	20010710		
			US 2001304241	P	20010710		
		<u> </u>	US 2001343710	P	20011026		
		<u> </u>	US 200237499	Α	20020102		
			US 2003387163	Α	20030311		
			US 2004815371	Α	20040331		
WO 2004082147	A2	20040923	WO 2004US6767	Α	20040305	200468	Е
EP 1618666	A2	20060125	EP 2004717990	Α	20040305	200608	E
		<u> </u>	WO 2004US6767	Α	20040305		
KR 2005118176	Α	20051215	WO 2004US6767	Α	20040305	200652	Е
			KR 2005716825	Α	20050909		
JP 2007525052	W	20070830	WO 2004US6767	Α	20040305	200759	Е
			JP 2006509171	Α	20040305		

Priority Applications (no., kind, date): US 2001296673 P 20010606; US 2001304131 P 20010710; US 2001304241 P 20010710; US 2001343710 P 20011026; US 200237499 A 20020102; US 2003387163 A 2003031; US 2004815371 A 20040331

				Pate	nt Details						
Patent Number Kind Lan Pgs Draw Filing Notes											
US 20040181666	A1	EN	41	19	Related to Provisional	US 2001296673					
					Related to Provisional	US 2001304131					

				Related to Provisional	US 2001304241
				Related to Provisional	US 2001343710
				C-I-P of application	US 200237499
				C-I-P of application	US 2003387163
WO 2004082147	A2	EN			
National Designated States,Original	DE D KP K NZ O	K DM E R KZ LO M PG P	Z EC EE C LK LR I H PL PT I	J AZ BA BB BG BR BW BY BZ C EG ES FI GB GD GE GH GM HE LS LT LU LV MA MD MG MK N RO RU SC SD SE SG SK SL SY T ZA ZM ZW	R HU ID IL IN IS JP KE KG IN MW MX MZ NA NI NO
Regional Designated States,Original				CZ DE DK EA EE ES FI FR GB L OA PL PT RO SD SE SI SK SL	
EP 1618666	A2	EN		PCT Application	WO 2004US6767
				Based on OPI patent	WO 2004082147
Regional Designated States,Original			G CH CY Γ RO SE S	CZ DE DK EE ES FI FR GB GR I SI SK TR	HU IE IT LI LT LU LV MC
KR 2005118176	Α	KO		PCT Application	WO 2004US6767
				Based on OPI patent	WO 2004082147
JP 2007525052	W	JΛ	32	PCT Application	WO 2004US6767
	1			Based on OPI patent	WO 2004082147

NOVELTY - The method involves determining whether a destination field of an Internet protocol (IP) header is loaded with a multicast IP address. An IP datagram having the IP header and a segmented body is produced. The produced IP datagram is transmitted from the head-end to a digital device e.g. personal computer and audio system. The segmented body includes a number of packets with identifiers. DESCRIPTION - One packet has an identifier that indicates a type of data stored in a payload of the packet, and the other packet with another identifier to indicate that the packet has content duplicative of content of former packet and cause the digital device to disregard the content. The latter packet is encrypted by a different key. An INDEPENDENT CLAIM is also included for a software packet filter program to perform a method of receiving content from a head-end by a digital device. USE - Used in terrestrial broadcast based content delivery system, Internet based content delivery, and satellite based content delivery system, for providing digital video and audio content from a head-end to a digital device e.g. PDA, personal computer, personal music player, audio system and digital recorder, over a network.

ADVANTAGE - The method transmits the digital audio and video content to the digital device along with the IP datagram, thus effectively securing the contents, and reducing the bandwidth requirements of the digital device.

DESCRIPTION OF DRAWINGS - The drawing shows a flow chart of a decryption process.

17/5/1 (Item 1 from file: 350) DIALOG(R)File 350: Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0013815306 Drawing available

WPI Acc no: 2003-492021/200346

Related WPT Ace No. 2000-672590; 2003-31163; 2003-331360; 2003-429690; 2003-556633; 2003-598999; 2003-618801; 2003-636908; 2003-709140; 2003-74465; 2003-778053; 2003-801037; 2003-801549; 2003-801728; 2003-854288; 2003-875004; 2004-031547; 2004-281382; 2004-281385; 2004-303692; 2004-303895; 2004-303896; 2004-339901; 2004-697671; 2005-194195; 2005-423462; 2005-629019; 2006-041350; 2006-530416; 2006-576334; 2006-600989; 2007-148599; 2007-173736; 2007-523208; 2007-673842; 2007-843365; 2008-A96344; 2008-F30393; 2008-F81867; 2008-M99741; 2009-F107993; 2009-6721130

Digital television signal encryption method for airline in-flight movie system, involves replacing unencrypted packets of predetermined packet type, with encrypted packets in TV signal to produce partially encrypted signal.

Patent Assignee: SONY ELECTRONICS INC (SONY); CANDELORE B L (CAND-I); UNGER R A (UNGE-I); SONY CORP (SONY)

Inventor: CANDELORE B L; UNGER R A

		Patent Fan	nily (9 patents, 101 cou	intries)	
Patent Number	Kind	Date	Application Number	Kind	Date	Update Type
US 20030026423	A1	20030206	US 2001296673	P	20010606	200346 B
			US 2001304131	P	20010710	
-			US 2001304241	P	20010710	
			US 2001343710	P	20011026	
			US 200238217	A	20020102	
CA 2405901	A1	20030426	CA 2405901	A	20021001	200346 E
WO 2003061289	A1	20030724	WO 2002US40050	A	20021213	200349 E
AU 2002360604	A1	20030730	AU 2002360604	A	20021213	200421 E
EP 1464174	A1	20041006	EP 2002795874	A	20021213	200465 E
			WO 2002US40050	A	20021213	
MX 2004006249	A1	20041101	WO 2002US40050	A	20021213	200558 E
			MX 20046249	A	20040624	
US 7336787	B2	20080226	US 200238217	A	20020102	200816 E
KR 2008110940	Α	20081219	WO 2002US40050	A	20021213	200919 E
			KR 2004710457	A	20040701	
			KR 2008730265	Α	20081211	
MX 257868	В	20080611	WO 2002US40050	Α	20021213	200941 E
			MX 20046249	Α	20040624	

Priority Applications (no., kind, date): US 2001296673 P 20010606; US 2001304131 P 20010710; US 2001304241 P 20010710; US 2001304241 P 20010710; US 2001304271 A 20020102; US 200238217 A 20020102; CA 2405901 A 20021001

Patent Details	***
Patent Number Kind Lan Pgs Draw Fili	ng Notes

US 20030026423	A1	EN	39	18	Related to Provisional	US 2001296673
					Related to Provisional	US 2001304131
					Related to Provisional	US 2001304241
					Related to Provisional	US 2001343710
CA 2405901	A1	EN				
WO 2003061289	A1	EN	1			
National Designated States,Original	DK E KZ L PL P	M DZ I C LK L	EC EE	ES FI C	Z BA BB BG BR BY BZ CA G GB GD GE GH GM HR HU II LV MA MD MG MK MN MV IG SK SL TI TM TN TR TT T	D IL IN IS JP KE KG KP KR V MX MZ NO NZ OM PH
Regional Designated States,Original					DK EA EE ES FI FR GB GH D SE SI SK SL SZ TR TZ UC	
AU 2002360604	A1	EN	T		Based on OPI patent	WO 2003061289
EP 1464174	A1	EN			PCT Application	WO 2002US40050
					Based on OPI patent	WO 2003061289
Regional Designated States,Original		T BE B T RO SI			DE DK EE ES FI FR GB GR	IE IT LI LT LU LV MC MK
MX 2004006249	A1	ES	T		PCT Application	WO 2002US40050
					Based on OPI patent	WO 2003061289
KR 2008110940	Α	KO			PCT Application	WO 2002US40050
	1		1		Division of application	KR 2004710457
					Based on OPI patent	WO 2003061289
MX 257868	В	ES			PCT Application	WO 2002US40050
	1		1		Based on OPI patent	WO 2003061289

NOVELTY - The unencrypted packets of data in digital television (TV) signal, are examined to identify predetermined packet type. The packets that are identified as predetermined packet type, are encrypted. The unencrypted packets of predetermined packet type is replaced with the encrypted packets in the digital TV signal, to produce a partially encrypted digital TV signal.

DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

- 1. electronic storage medium storing digital television signal encrypting program;
- electronic transmission medium;
- encrypted television program;
- television set-top box;
- partially encrypted television program decoding method;
- information stream encryption method using packets;
- 7. packetized digital content manipulation method; and
- 8. multiple conditional access providers allowing method.

USE - For encrypting digital television signal in entertainment system e.g. airline in-flight movie system. ADVANTAGE - Allows the digital television signal to be efficiently encrypted, by replacing the

unencrypted packets with the encrypted packets.
DESCRIPTION OF DRAWINGS - The figure shows the block diagram of the decoder chip.

17/5/3 (Item 3 from file: 350)

DIALOG(R)File 350: Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0013703918 Drawing available

WPI Acc no: 2003-801037/200375

Related WPI Ace Ne: 2000-672590; 2003-311631; 2003-331360; 2003-499609; 2003-492021; 2003-556633; 2003-598999; 2003-618801; 2003-69098; 2003-79140; 2003-74465; 2003-778053; 2003-801549; 2003-801728; 2003-851288; 2003-875064; 2004-031547; 2004-2481382; 2004-2481385; 2004-303692; 2004-303895; 2004-303896; 2004-339901; 2004-697671; 2005-194195; 2005-423462; 2005-629019; 2006-601350; 2006-536416; 2006-576334; 2006-600989; 2007-148599; 2007-157336; 2007-523208; 2007-673842; 2007-843365; 2008-896344; 2008-F30393; 2008-F81867; 2008-M99741; 2009-F107993; 2009-6721130

Partially encrypted television program decoding method involves decrypting encrypted packets having secondary packet identifier and decoding decrypted packets along with unencrypted packets having primary packet identifier

Patent Assignee: SONY ELECTRONICS INC (SONY); CANDELORE B L (CAND-I); UNGER R A (UNGE-I); SONY CORP (SONY)

Inventor: CANDELORE B L; PEDLOW L M; UNGER R A

		Patent Fa	mily (3 patents, 2 cour	ntries)		
Patent Number	Kind	Date	Application Number	Kind	Date	Update Type
US 20020196939	A1	20021226	US 2001296673	P	20010606	200375 B
			US 2001304131	P	20010710	
			US 2001304241	P	20010710	
			US 200237498	A	20020102	
CA 2406329	A1	20030426	CA 2406329	Α	20021001	200375 E
US 7127619	B2	20061024	US 2001296673	P	20010606	200670 E
			US 2001304131	P	20010710	
			US 2001304241	P	20010710	
			US 2001343710	P	20011026	
			US 200237498	A	20020102	

Priority Applications (no., kind, date): US 2001296673 P 20010606; US 2001304131 P 20010710; US 2001304241 P 20010710; US 2001343710 P 20011026; US 200237498 A 20020102

			I	Patent I	Details	
Patent Number	Kind	Lan	Pgs	Draw	Filing Notes	
US 20020196939	A1	EN	37	18	Related to Provisional US 200129667	3
					Related to Provisional US 200130413	1
					Related to Provisional US 200130424	1
CA 2406329	A1	EN				
US 7127619	B2	EN			Related to Provisional US 200129667	3
					Related to Provisional US 200130413	1
	T				Related to Provisional US 200130424	1
					Related to Provisional US 200134371	0

NOVECTY - A partially encrypted television program is identified by unencrypted and encrypted packets associated with a primary packet identifier and a secondary packet identifier, respectively. The packets having secondary packet identifier are decrypted. The decrypted packets are decoded along with packets having primary packet identifier.

DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

- 1. partially encrypted television signals decoding method;
- 2. partially encrypted television program decoding method;
- television;
- content player;
- television set top box;
- decoding circuit; and
- packets processing method.

USE - For decoding partially encrypted content such as television signals.

ADVANTAGE - Since only a portion of the program is encrypted, less bandwidth is consumed, thus large number of programs are carried over the same bandwidth, while permitting coexistence of multiple conditional access system in a single cable television system.

DESCRIPTION OF DRAWINGS - The figure shows the block diagram of the decoder chip.

1014,1032,1052 buffers

1018 MPEG audio decoder

1036,1056 MPEG video decoder

17/5/4 (Item 4 from file: 350)

DIALOG(R)File 350: Derwent WPIX

(c) 2009 Thomson Reuters. All rights reserved.

0013465100 Drawing available

WPI Acc no: 2003-556633/200352

Related WPI Acc No: 2000-672590; 2003-331360; 2003-429690; 2003-492021; 2003-598999; 2003-618801; 2003-636908; 2003-709140; 2003-744465; 2003-78903; 2003-801037; 2003-801549; 2003-8010378; 2003-854288; 2003-875004; 2004-031547; 2004-281382; 2004-281385; 2004-303692; 2004-303895; 2004-303896; 2004-339901; 2004-697671; 2005-194195; 2005-423462; 2005-629019; 2006-4031562; 2006-536416; 2006-576334; 2006-60999; 2007-148599; 2007-157336; 2007-522308; 2007-673342; 2007-843365; 2008-896344; 2008-F30393; 2008-F81867; 2008-M99741; 2009-F10793; 2009-6721130

Digital television signal encryption method for use in e.g. digital cable system, involves encrypting audio packets that are identified by using packet identifier, according to different encryption methods

Patent Assignee: SONY ELECTRONICS INC (SONY); CANDELORE B L (CAND-I); SONY CORP (SONY)

Inventor: CANDELORE B L; EYER M K; MIRSKY G; PEDLOW L M; UNGER R A

		Patent Fa	mily (4 patents, 3 cour	ntries)			
Patent Number	Kind	Date	Application Number	Kind	Date	Update	Туре
US 20030081776	A1	20030501	US 2001296673	P	20010606	200352	В
			US 2001304131	P	20010710		
-			US 2001304241	P	20010710		
			US 200237914	A	20020102		
CA 2405865	A1	20030426	CA 2405865	Α	20021001	200352	E
CN 1633809	A	20050629	CN 2002828452	A	20021213	200574	Е
US 7124303	B2	20061017	US 2001296673	P	20010606	200668	Е
			US 2001304131	P	20010710		
			US 2001304241	P	20010710		
		***************************************	US 2001343710	P	20011026		
			US 200237914	A	20020102		

Priority Applications (no., kind, date): US 2001296673 P 20010606; US 2001304131 P 20010710; US 2001304241 P 20010710; US 2001343710 P 20011026; US 200237914 A 20020102; CA 2405865 A 20021001

			1	Patent I	Details	
Patent Number	Kind	Lan	Pgs	Draw	Filing No	otes
US 20030081776	A1	EN	38	18	Related to Provisional	US 2001296673
					Related to Provisional	US 2001304131
					Related to Provisional	US 2001304241
CA 2405865	A1	EN				
US 7124303	B2	EN			Related to Provisional	US 2001296673
					Related to Provisional	US 2001304131
	[-		Related to Provisional	US 2001304241

	1	- 1	-	Related to Provisional US 2001343710	
ŝ	1 1	3	- 3	Related to Provisional (US 2001545/10)	

NOVELTY - Audio packets of a digital television signal, that are to be encrypted are identified, using packet identifier. The identified audio packets are encrypted according to different encryption methods, to produce respective encrypted audio portions. Unencrypted video portion of the television signal, is combined with the encrypted audio portions.

DESCRIPTION - INDEPENDENT CLAIMS are also included for the following:

- 1. electronic storage medium storing program for encrypting digital television signal;
- 2. electronic transmission medium carrying encrypted television signal;
- television set-top box;
- cable system headend; and
- 5. television signal decoding method.

USE - In digital audio/video system, digital cable system, terrestrial broadcast based content delivery system, internet- based content delivery system and satellite-based content delivery system. ADVANTAGE - Enhances the security of encryption and reduces bandwidth overhead. DESCRIPTION OF DRAWINGS - The figure shows the flowchart of dual encryption method.

[bad date, fvi]

24/5/5 (Item 5 from file: 350) DIALOG(R)File 350: Derwent WPIX

(c) 2009 Thomson Reuters, All rights reserved.

0013042068 Drawing available

WPI Acc no: 2003-121356/200311

XRPX Acc No: N2003-096615

Transmitting data frames e.g. for Internet applications using stream-cipher information embedded redundantly in next packet of encrypted frame Patent Assignee: KONINK PHILIPS ELECTRONICS NV (PHIG); VAN PUL C L M (VPUL-I); VAN

RIJNSOEVER B J (VRIJ-I)

Inventor: VAN PUL C; VAN PUL C L M; VAN RIJNSOEVER B; VAN RIJNSOEVER B J; VAN P C L Patent Family (10 patents, 24 countries)

Patent Number	Kind	Date	Application Number	Kind	Date	Update	Туре
WO 2003005635	A2	20030116	WO 2002IB2393	Α	20020620	200311	В
DE 60224803	T2	20090122	DE 60224803	Α	20020620	200907	Е
			EP 2002738488	Λ	20020620		
***************************************		<u> </u>	WO 2002IB2393	Α	20020620		
KR 2003045055	Α	20030609	KR 2003703338	Α	20030306	200370	Е
EP 1407574	Λ2	20040414	EP 2002738488	Α	20020620	200426	E
			WO 2002IB2393	Α	20020620		
US 20040165722	A1	20040826	WO 2002IB2393	Α	20020620	200457	Е
			US 2003482145	Α	20031222		
JP 2004534479	W	20041111	WO 2002IB2393	Α	20020620	200474	Е
			JP 2003511472	Α	20020620		
CN 1524362	Λ	20040825	CN 2002813511	Α	20020620	200477	E
EP 1407574	B1	20080123	EP 2002738488	Α	20020620	200810	Е
			WO 2002IB2393	Α	20020620		
DE 60224803	Е	20080313	DE 60224803	Α	20020620	200821	Е
			EP 2002738488	Α	20020620		
			WO 2002IB2393	Α	20020620		
JP 4083678	B2	20080430	WO 2002IB2393	Λ	20020620	200831	Е
			JP 2003511472	Α	20020620		

Priority Applications (no., kind, date): EP 2001202608 A 20010706

Patent Details							
Patent Number	Kind	Lan	Pgs	Draw	Filing Notes		
WO 2003005635	A2	EN	10	4			
National Designated States, Original	CN JI	KR U	S				
Regional Designated	AT B	E CH (CY D	E DK ES FI F	R GB GR IE IT LU MC NL PT SE TR		

States,Original								
DE 60224803	T2	DE		Application	EP 2002738488			
				PCT Application	WO 2002IB2393			
				Based on OPI patent	EP 1407574			
				Based on OPI patent	WO 2003005635			
EP 1407574	A2	EN		PCT Application	WO 2002IB2393			
				Based on OPI patent	WO 2003005635			
Regional Designated States,Original	AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR							
US 20040165722	A1	EN		PCT Application	WO 2002IB2393			
JP 2004534479	W	JA	23	PCT Application	WO 2002IB2393			
				Based on OPI patent	WO 2003005635			
EP 1407574	B1	EN		PCT Application	WO 2002IB2393			
				Based on OPI patent	WO 2003005635			
Regional Designated States,Original	AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR							
DE 60224803	E	DE		Application	EP 2002738488			
				PCT Application	WO 2002IB2393			
				Based on OPI patent	EP 1407574			
				Based on OPI patent	WO 2003005635			
JP 4083678	B2	JA	7	PCT Application	WO 2002IB2393			
				Previously issued patent	JP 2004534479			
		TT		Based on OPI patent	WO 2003005635			

NOVELTY - Involves frame-based information being transmitted through a transmission medium, whilst payload information of a particular frame is assigned to several transmission packets. The payload information of the frame is encrypted using a frame encryption key. Each transmission packet has individual stream-cipher-based synchronization information that, in combination with the frame decryption key, enables the associated encrypted transmission packet to be decrypted.

DESCRIPTION - The stream-cipher-based synchronization information is transmitted by redundantly including it in a second transmission packet next to the first packet. The stream-cipher-based synchronization information operates as seed information for decrypting the second transmission packet. INDEPENDENT CLAIMs are included for a device, a system, a medium, a computer program and a transmitted size and.

USE - To provide secure streamed content to user's over the internet, such that the content cannot be illegally accessed or copied.

 $ADVANTAGE-Enables \ more \ reliable \ reception \ of sequence \ of \ individual \ decryption \ synchronizing \ information \ packets \ for \ improved \ transmission \ of e.g. \ streaming \ video.$

DESCRIPTION OF DRAWINGS - The drawing shows the frame structure employed by the method.

FULL-TEXT PATENTS

17/3K/5 (Item 3 from file: 349) DIALOG(R)File 349: PCT FULLTEXT (c) 2009 WIPO/Thomson. All rights reserved.

00571790

A METHOD FOR OPTIMIZING OF DATA TRANSMISSION PROCEDE POUR OPTIMISER LA TRANSMISSION DE DONNES

Patent Applicant/Patent Assignee:

- NOKIA MOBILE PHONES LTD
- RUUTU Jussi
- MA Jian

Inventor(s):

- RUUTU Jussi
- MA Jian

	Country	Number	Kind	Date	
Patent	WO	200035163	A1	20000615	
Application	wo	99FI1008		19991207	
Priorities	FI	982651		19981208	

Designated States: (Protection type is "Patent" unless otherwise stated - for applications prior to 2004)
AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM,
EE, ES, FI, GB, GD, GE, GH, GM, HR, HU,
ID, HL, IN, IS, P, KE, KG, FW, RR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, NO, NZ, PL, FT, RO, RU,
SD, SE, SG, SI, SK, SL, TJ, TM, TM, TT,
TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, GH,
GM, KE, LS, MW, SD, SI, SZ, TZ, UG, ZW,
AM, AZ, BY, KG, KZ, MD, RU, TI, TM, AT,
BE, CH, CY, DE, DK, ES, FI, FR, GB, GR,
IE, TL, LU, MC, NI, PT, FS, BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN,
TD, TG

6493

Language Publication Language: English Filing Language:

Fulltext word count:

Claims:

...method according to claim 9, characterized in that said destination network element uses said modified copy of the information instead of the encrypted version of the information carried as the payload of the IP datagram. 1 I. A method according to claim 1, be used in congestion control 'in a ...

[date?]

16/5/5 (Item 2 from file; 23) DIALOG(R)File 23: CSA Technology Research Database (c) 2009 CSA, All rights reserved.

0012384940 IP Accession No: 200909-71-1242678; 200909-61-1267059; 20091236013; A09-99-1719022

Processing an MPEG elementary stream in a conditional access overlay environment

Pinder, Howard G; Hopper, Jeffrey C

TISA

Publisher Url: http://patft.uspto.gov/netacgi/nph-Parser?Sect1=PTO2&Sect2=HTTOFF&u=/netaht ml/PTO/search-adv.htm&r=1&p=1&f=G&l=50&d=PTXT&S1=75-55123.PN.&OS=pu/7555123& RS=PN/7555123

Document Type: Patent

Record Type: Abstract

Language: English

File Segment: Metadex; Mechanical & Transportation Engineering Abstracts; ANTE: Abstracts in New Technologies and Engineering; Aerospace & High Technology

Abstract:

Processing an MPEG elementary stream contained in multiple PID streams in a conditional access overlay environment. A multi-program transport stream contains numerous video and audio elementary streams. Critical packets in the elementary streams are encrypted with two different encryption schemes creating a stream having multiple PID values. The streams are then sent from the headend to individual set-top boxes. One encryption scheme can be decoded by the incumbent set-top box and the second encryption scheme can be decoded by the overlay set-top box. The overlay set-top box uses a dual filter system to filter and decode the PIDs for each video and audio stream of the desired program.

Descriptors: Streams; Encryption; Sound filters; Video compression; Conditional access; Proportional integral derivative; MPEG encoders; Transport Subj Catg; 71, General and Nonclassified; 61, Design Principles; 99, General

[date?]

16/5/6 (Item 3 from file: 23)

DIALOG(R)File 23: CSA Technology Research Database

(c) 2009 CSA. All rights reserved.

0011692501 IP Accession No: 200904-71-0775096; 200904-61-0789502; 20090763210; A09-99-0765065

Conditional access overlay partial encryption using MPEG transport continuity counter

Wasilewski, Anthony J

. USA

Publisher Url: http://patft.uspto.gov/netacgi/nph-Parser?Sect1=PTO2&Sect2=HITOFF&u =/netaht ml/PTO/search-adv.htm&r=1&p=1&f=G&l=50&d=PTXT&S1=74 90236.PN.&OS=pn/7490236& RS=PN/7490236

Document Type: Patent

Record Type: Abstract

Language: English

File Segment: Metadex; Mechanical & Transportation Engineering Abstracts; ANTE: Abstracts in New Technologies and Engineering; Aerospace & High Technology

Abstract:

A conditional access overlay system utilizing partial encryption without requiring additional program identifiers. The conditional access overlay system generates duplicate critical packets for separate encryption that are sent using the same packet identifier. The rest of the content stream is sent in the clear. However, these duplicated packets are sent without incrementing a continuity counter relative to one another. The overlay packets with non-incremented continuity counter are sent as the second packet immediately following the original critical packet. At the receivers, the incumbent set-top will use the first of the two encrypted packets while the overlay set-top is programmed to use the second of the two encrypted packets. Therefore, methods for verifying alignment of associated packets may be used to distinguish between multiple encryption methods in conditional access overlay systems.

Descriptors; Conditional access; Encryption; Continuity; Reproduction; MPEG encoders; Streams; Receivers: Transport: Rest: Video compression: Alignment

Subj Catg: 71, General and Nonclassified; 61, Design Principles; 99, General

[date?]

16/5/9 (Item 6 from file: 23)

DIALOG(R)File 23: CSA Technology Research Database

(c) 2009 CSA. All rights reserved.

0009650346 IP Accession No: 200807-71-0864988; 200807-61-0965518; 20080831284; A08-99-0935220

Video slice and active region based multiple partial encryption

Candelore, Brant L; Derovanessian, Henry; Pedlow Jr, Leo M . USA

Publisher Url: http://patft.uspto.gov/netacgi/nph-Parser?Sect1=PTO2&Sect2=HTTOFT&u =/netaht ml/PTO/search-adv.htm&r=1&p=1&f=G&l=50&d=PTXT&S1=73 76233.PN.&OS=pn/7376233&RS=Pn/7376233

Document Type: Patent Record Type: Abstract

Language: English

File Segment: Metadex; Mechanical & Transportation Engineering Abstracts; ANTE: Abstracts in New Technologies and Engineering; Aerospace & High Technology

Abstract:

A selective encryption encoder and method of dual selective encryption. The selective encryption encoder has a packet identifier that identifies packets of at least one specified packet type, the at least one specified packet type being any of a plurality of packet types including packets containing a video slice headers or packets carrying data appearing in an active area of the image. A packet duplicator duplicates the identified packets to produce first and second sets of the identified packets. The packets are sent to and from a primary encryption encoder to encrypt the first set of identified packets under a first encryption method. A secondary encrypter encrypts the second set of identified packets under a first encryption method.

Descriptors: Encryption; Coders; Encoders; Reproduction; Images; Headers Subj Catg: 71, General and Nonclassified; 61, Design Principles; 99, General

[bad date - 3/16/2004 - fyi]

16/5/10 (Item 7 from file: 23)

DIALOG(R)File 23: CSA Technology Research Database

(c) 2009 CSA. All rights reserved.

0009076943 IP Accession No: 200805-71-628148; 200805-61-676809; 2008608898; A08-99-658030 Dynamic composition of pre-encrypted video on demand content

Pedlow Jr, Leo M; Agnihotri, Davender

. USA

Publisher Url: http://patft.uspto.gov/netaegi/nph-Parser/Sect1=PITO2&Sect2=HITO1F&u=/netaht ml/PTO/Search-adv./htm&r=1&p=1&f=G&1=50&d=PTXT&S1=73 46163.PN.&OS=pu/7346163& RS=PN/7346163

Document Type: Patent Record Type: Abstract Language: English

File Segment: Metadex; Mechanical & Transportation Engineering Abstracts; ANTE: Abstracts in New Technologies and Engineering; Aerospace & High Technology

Abstract:

According to certain embodiments consistent with the present invention, a method of processing digital video content, wherein the digital video content comprises intra-coded frames and inter-coded frames, involves selecting a plurality of the intra-coded frames for encryption to produce selected frames; encrypting the selected frames under a first encryption algorithm to produce first encryption frames in a first file; and storing the intra-coded frames, whether encrypted under the first encryption algorithm or unencrypted, in a second file. For a multiple encryption embodiment consistent with the present invention, the method further involves duplicating the intra-coded frames; encrypting duplicates of the selected frames under a second encryption algorithm to produce second encrypted frames; storing the intra-coded frames, whether encrypted under the second encryption algorithm or unencrypted, in a third file. This abstract is not to be considered limiting, since other embodiments may deviate from the features described in this abstract.

Descriptors: Frames; Encryption; Algorithms; Storage; Inventions; Reproduction; Constraining; Dynamics; Video on demand

Subj Catg: 71, General and Nonclassified; 61, Design Principles; 99, General

16/5/11 (Item 8 from file: 23)

DIALOG(R)File 23: CSA Technology Research Database

(c) 2009 CSA, All rights reserved.

0008891554 IP Accession No: 200804-71-466978; 200804-61-494336; 2008451369; A08-99-481143 Method and apparatus for providing conditional access in connection-oriented, interactive networks with a multiplicity of service providers

Wasilewski, Anthony John; Woodhead, Douglas F; Logston, Gary Lee

, USA

Publisher Url: http://patft.uspto.gov/netaegi/nph-Parser/Sect1=PITO2&Sect2=HITO1F&u=/netaht ml/PTO/Search-adv./htm&r=1&p=1&f=G&l=50&d=PTXT&S1=58 70474.PN.&OS=pu/5870474& RS=PN/5870474

Document Type: Patent Record Type: Abstract Language: English

File Segment: Metadex; Mechanical & Transportation Engineering Abstracts; ANTE: Abstracts in New Technologies and Engineering; Aerospace & High Technology

Abstract:

A control system provides secure transmission of programs, including at least one of video, audio, and data, between a service provider and a customer's set top unit over a digital network. Program bearing data, packets are recieved in a first network protocol over a first data link and removed from the first network protocol. Packets representing a particular program requested by a customer having a set top unit are elected. Conditional access is provided to the selected program. In particular, program bearing packets are encrypted according to a first encryption algorithm using a first key, which is then encrypted according to a second encryption algorithm using a second key. The first keys are transported in packets to the customer's set top units along with the program packets. A public key cryptographic technique encrypts the second key such that the public key used in the encryption corresponds to the private key of the customer's set top unit. After the conditional access layers have been added, the packets are encapsulated and output in a second network protocol destined for the set top unit.

Descriptors: Networks; Conditional access; Encryption; Algorithms; Bearing; Encapsulation; Cryptography; Data links; Keys; Control systems; Customer satisfaction; Genetic algorithms Subj Catg; 71, General and Nonclassified; 61, Design Principles; 99, General